

# Saratoga County Inter-Municipal Stormwater Management (ISWM) Program

*A partnership to protect water quality*

A number of communities and government agencies in Saratoga County have joined together to develop a stormwater management program to protect our waterways and enhance our quality of life. The goal of the ISWM Program is to utilize County-wide collaboration to identify existing resources and develop programs to reduce the negative impacts of stormwater pollution.

The ISWM Program meets monthly to develop and implement a stormwater management program which complies with New York State's Phase II Stormwater regulations.

## **Members**

Saratoga County Cornell Cooperative Extension

Ballston (T)  
Ballston Spa (V)  
Charlton (T)  
Clifton Park (T)  
Greenfield (T)  
Halfmoon (T)  
Malta (T)  
Mechanicville (C)  
Milton (T)  
Moreau (T)  
Round Lake (V)  
Saratoga County  
Saratoga Springs (C)  
Stillwater (T)  
Stillwater (V)  
Waterford (T)  
Waterford (V)  
Wilton (T)

## **Support**

Saratoga County Soil and Water Conservation District

For information about the ISWM Program and how it is working to address the requirements of the Phase II Stormwater Rule, contact us at (518) 885-8995 or visit [www.saratogastormwater.org](http://www.saratogastormwater.org)



Saratoga County Inter-Municipal Stormwater Management Program

## Pools, Fountains & Spas...

### How to Prevent Water & Storm Sewer Pollution

#### Best Management Practices for:

- Homeowners
- Condominium & Apartment Complexes
- Hotels, Motels and Inns
- Schools
- Fitness Clubs



Saratoga County Inter-Municipal Stormwater Management Program

## Stormwater Pollution

### What is Stormwater?

Stormwater is water from rain or melting snow that does not soak into the ground. It flows from rooftops, over paved areas, bare soil, and sloped lawns. As it flows, stormwater runoff collects and transports soil, animal waste, salt, pesticides, fertilizers, oil and grease, debris and other potential pollutants.

### What is the Problem?

Rain and snowmelt wash pollutants from streets, construction sites, and land into storm sewers and ditches. Eventually, the storm sewers and ditches empty the polluted stormwater directly into streams and rivers with no treatment. This is known as *stormwater pollution*.

Polluted stormwater degrades our lakes, rivers, wetlands and other waterways. Nutrients such as phosphorous and nitrogen can cause the overgrowth of algae resulting in oxygen depletion in waterways. Toxic substances from motor vehicles, and careless application of pesticides and fertilizers threaten water quality and can kill fish and other aquatic life. Bacteria from animal wastes and improper connections to storm sewer systems can make lakes and waterways unsafe for wading, swimming and fish consumption. Eroded soil is a pollutant as well. It clouds the waterway and interferes with the habitat of fish and plant life.

Fortunately, stormwater pollution can be prevented or minimized by implementing Stormwater Management Practices which are procedures or activities that reduce or eliminate pollutants in stormwater.



## How to Prevent Pollution from Pools, Spas & Fountains

Although we enjoy the fun and relaxing times in them, the water used in swimming pools, spas and fountains can cause problems for our creeks and lakes if not disposed of properly. Draining your pool, spa or fountain improperly can result in chlorine, suspended solids and nutrients entering surface water (streams and lakes).

### Best Management Practices

Best Management Practices or BMPs are procedures that help to prevent pollutants like chlorine and sediment from entering storm drains.

#### Draining Pools, Spas and Fountains:

- Never discharge pool, spa, or fountain to a street or storm drain; discharge to a sanitary sewer cleanout.
- If possible, when emptying a pool, spa or fountain, let chlorine dissipate for a few days and then recycle/reuse water by draining it gradually onto a landscaped area.
- Drain pools, spas and fountains slowly, using a low volume pump or siphon.

## Best Management Practices (continued)

- Make sure water used to acid wash pool, spa or fountain is neutralized prior to discharge. Soda ash can be used to keep the pH between 6.0 and 7.0 before discharging.
- Do not use copper-based algaecides. Control algae with alternatives such as sodium bromide.

#### Filter Cleaning:

- Never clean a filter in the street or near a storm drain. Rinse cartridge and diatomaceous earth filters onto a dirt area and spade filter residue into soil. Dispose of spent diatomaceous earth in the garbage.
- If there is no suitable lawn area, call your local wastewater treatment plant for instructions on discharging filter backwash or rinse water to the sanitary sewer.

